



InternationalLight
TECHNOLOGIES

ISO9001:2008

FLEX 60 & 120 ACCENT/COVE LIGHTING

APPLICATION:

- Back lighting panel
- Edge lighting for a variety of objects
- Cove lighting
- Indirect accent decorative lighting in commercial and residential applications
- Signage applications
- Ideal for architectural and landscape lighting



GTL-FLEX-60-W-3000k

FEATURE:

- Makes use of 2.5mm height SMD LED which can be used in small areas
- 5mm wide PCB can be specially ordered
- Flexible circuit board with 3M self-adhesive backing for easy install
- Available in 5 meter and 10 meter reels
- Available in warm whites of 4800K and 3000K

Specifications:

Part No.	Operating Voltage (V)	Current (mA)	Power dissipation (W)	Emitting color	Peak wavelength (nm)	Viewing Angle	Luminous flux		LED quantity (pc)	Measure L*W (mm)
							(lm)			
							min	max		
GTL-FLEX-60-R	12	400	4.8	Red	626	140	42	60	60	1000*8
GTL-FLEX-60-Y	12	400	4.8	Yellow	590	140	42	60	60	1000*8
GTL-FLEX-60-B	12	400	4.8	Blue	470	140	30	36	60	1000*8
GTL-FLEX-60-G	12	400	4.8	Green	525	140	72	96	60	1000*8
GTL-FLEX-60-W-6000k	12	400	4.8	White	6000k	140	84	104	60	1000*8
GTL-FLEX-120-R	12	800	9.6	Red	626	140	84	120	120	1000*8
GTL-FLEX-120-Y	12	800	9.6	Yellow	590	140	84	60	120	1000*8
GTL-FLEX-120-B	12	800	9.6	Blue	470	140	60	72	120	1000*8
GTL-FLEX-120-G	12	800	9.6	Green	525	140	144	192	120	1000*8
GTL-FLEX-120-W-6000k	12	800	9.6	White	6000k	140	168	208	120	1000*8

GTL-FLEX-120 & 60 Mechanical Detail

