

"SUMMIT" Series ILT-PC-2X2



ILT INNOVATIONS

Products • Capabilities • Applications

InternationalLight
TECHNOLOGIES

International Light Technologies has provided innovative design and engineering solutions for LED lighting applications for 50 YEARS.

Let us provide you the quality, performance and cost-effective LED solutions you require.

Applications:

- Internally Illuminated Sign Cabinets
- Channel Letters: Face and Halo
- Architectural Lighting
- Cove and Accent Lighting

Features:


- 4 5050 SMD LED's per module.
- 2 modules per ft, 25ft per strip.
- 3M VHB double faced tape.
- Mechanical fasteners for a secure installation included.
- Low power draw, 30 ft of modules on a 12 volt 60 watt power supply.
- Lumen output for White: 160 lm per foot.
- Controlled color consistency, 6500K color temperature.
- Constant Current Technology on the Board.
- NEMA 6-6p or IP67 Rated.
- UL Recognized in US and Canada.

Specifications:


| Part# | Description | Operating Voltage | Current (mA) | Wattage | LEDs / Module | Color Peak Wavelength (nm) | Beam Angle | Module Dimensions (LxWxH) | Luminous Flux/Foot | Qty 60 Watt Power Supply |
|--------------|---------------------------|-------------------|--------------|---------|---------------|----------------------------|------------|---------------------------|--------------------|--------------------------|
| ILT-PC-2X2-W | Cold White SMD LED Module | 12V | 80 | 0.96 | 4 | White (6500) | 140 | 1.75"x1.5"x0.314" | 160 | 58 modules |
| ILT-PC-2X2-R | Red SMD LED Module | 12V | 80 | 0.96 | 4 | Red (623) | 140 | 1.75"x1.5"x0.314" | 72 | 58 modules |

Special Order on Summit Series - Amber, Yellow, Green and Blue. 4 to 6 week Lead Time.

Mechanicals:



Circuit Diagram:



For additional information call:
Joe Reis at 978-818-6180 ext 214
For a Quote and Population
layout, send PDF, drawings to:
jreis@intl-lighttech.com

10 Technology Drive, Peabody, MA 01960
978-818-6180 fax: 978-818-6181
www.intl-lighttech.com